



Jeep JK and JL

Thank you for ordering brackets from ExtendMySeat, the automotive solution for more leg-room, more comfort and better driving.

*Inventory in Box:*

**3- ExtendMySeat brackets**

**3- 3/8 x 3/4" Black Bolts**

**1- 3/6" x 17/64" Hex Lock Nut**

What you will need for assembly:

**1- Socket wrench**

**1- Phillips Head Screwdriver**

Step 1- Remove the Black ExtendMySeat brackets from the package and bolt package.

Step 2- Use a socket to remove the two factory bolts in the front seat then slide your seat forward. The bolt might require a torque wrench to loosen due to high tension.

Step 3 - Move to the backseat to locate and remove the two rear factory bolts.

Step 4- Slide the 3 brackets under the factory seat from the front. The largest bracket is the outer bracket. The middle sized bracket is the front inner and the smallest is the rear inner.

Step 5- Lay down the ExtendMySeat brackets down on the floorboard.

Step 6- Starting in front, finger tighten the brackets to the floorboard using the factory bolts. This should secure the brackets to the floorboard.

Step 7- Now slightly tighten the two front seat "feet" into the new ExtendMySeat hole locations using the black ExtendMySeat bolts.

Step 8- Slide the seat all the way forward and go to the back seat to secure the remaining two factory "feet" with the one 3/8' x 3/4" bolt for the outer bracket and use the Hex Lock Nut for the rear inner bolt. .

Step 10- Complete the installation by securing the eight bolts. Check to make sure all eight bolts are tight and secure.

Step 11- Test seat by sliding it back and forth. You are complete.

NOW, ENJOY!!!!

-ExtendMySeat Team

