

Toyota Prius 4 2016-Present Toyota Camry 2017-Present Thank you for ordering brackets from ExtendMySeat, the automotive solution for more leg-room, more comfort and better driving.

Inventory in Box:

- 2- ExtendMySeat brackets
- 2- M10 x 1.25" Flat Head Screws
- 4-3/8 x 1" Flat Head Screws
- 2-3.8" x 34" Black Hex Screws

What you will need for assembly:

- 1- Socket wrench
- 1- Torx 50 head
- 1- Phillips Head Screwdriver
- Step 1- Remove the Black ExtendMySeat brackets from the package and bolt package.
- Step 2- Use a Torx 50 socket to remove the two factory bolts in the front seat then slide your seat forward. The bolt might require a torque wrench to loosen due to high tension.
- Step 3 Move to the backseat and remove the plastic guards then locate and remove the two rear factory bolts.
- Step 4- Slide the 2 brackets under the factory seat from the rear.

Step 5- Lay down the ExtendMySeat brackets down on the floorboard. The small 90 degree bends face the rear of the car.



Step 6- Starting in rear, tighten the brackets to the floorboard using the factory bolts. This should secure the brackets to the floorboard.

Step 7- Move to Front, finger tighten the brackets to the floorboard using the factory

bolts. This should secure the brackets to the floorboard. Now slightly tighten the two front seat "feet" into the new ExtendMySeat hole locations using the shorter silver 3/8" x 1" ExtendMySeat bolts.

Step 8- Slide the seat all the way forward and go to the back seat to secure the remaining two factory "feet" with the two 3/8' x 1" Bolts.

Step 9- Go to the rear and align the factory seat with the new ExtendMySeat hole locations. Slightly tighten the two rear seat "feet" into the new ExtendMySeat hole locations using the shorter silver 3/8" x 1" ExtendMySeat bolts.

Step 11- Complete the installation by securing the eight bolts. Check to make sure all eight bolts are tight and secure.

Step 12- Test seat by sliding it back and forth. You are complete.

NOW, ENJOY!!!!

Best,