

Thank You

Thank you for ordering brackets from ExtendMySeat, the automotive solution for more leg-room, more comfort and better driving.

Inventory in Box:

- 2 - ExtendMySeat brackets
- 2 - Black 3/8 bolts
- 2 - Stainless 3/8 bolts

What you will need for assembly:

- 1 - Socket wrench
- 1 - Metric 14 socket

STEP 1

Remove the ExtendMySeat brackets from the package and locate the bolts provided.

STEP 2

Use a 14 socket to remove the two factory bolts in the front seat of the car then slide your seat all the way forward.

STEP 3

Move to the backseat and remove the two plastic guards then locate and remove the two rear factory bolts.

STEP 4

Move your seat all the way back to lift the front of your seat up so you can slide the ExtendMySeat brackets under the seat.

STEP 5

Lay down the two ExtendMySeat brackets under the seat so the four factory holes align (you can choose to remove your seat, but it is not necessary)

For 4Runner installation the ExtendMySeat brackets need to be installed with the 90 degree bends facing inward.

For Rav4 installation the ExtendMySeat brackets need to be installed with the 90 degree bends facing **outward**



STEP 6

Tighten the factory bolts into the front and rear ExtendMySeat bracket holes.

(Note: You might need to cut your carpet for ease of installation)



STEP 7

Insert factory seat on top of the ExtendMySeat brackets to align with front holes. Tighten front two "feet" with provided black ExtendMySeat bolts.



STEP 8

Press seat lever and slide seat to the most up front position. Go to back seat and screw down the two remaining factory feet with the stainless ExtendMySeat bolts.



Rear View

STEP 9

Make sure all eight bolts (four factory and four ExtendMySeat) are tight and secure.

STEP 10

Test seat by sliding it back and forth. You are now complete.

MORE INFORMATION

To view a video on installation, please visit extendmyseat.com/install-guides/

EXTENDMYSEAT.COM
3186-H Airway Avenue
Costa Mesa, California 92626