

### Thank You

Thank you for ordering brackets from ExtendMySeat, the automotive solution for more leg-room, more comfort and better driving.

### Inventory in Box:

4- ExtendMySeat brackets  
3- Black 3/8 bolts  
1- 3/8 nut

### What you will need for assembly:


1- Socket wrench  
1- Metric 14 socket  
1- Metric 14 flat wrench

### STEP 1

Remove the four ExtendMySeat brackets from the package and locate the three black 3/8 bolts and hex nut provided.

### STEP 2

Use a 14 socket to remove the two factory bolts in the front seat of the car then slide your seat all the way forward.



### STEP 3


Move to the backseat and remove the two plastic guards then locate and remove the two rear factory bolts.

### STEP 4

Move your seat all the way back to lift the front of your seat up so you can slide the ExtendMySeat brackets under the seat.

### STEP 5


Lay down the four ExtendMySeat brackets under the seat so the four factory holes align (you can choose to remove your seat, but it is not necessary) See photo above to identify locations of four parts.



### STEP 6

(Rear/backseat photo)

Start by slightly tightening the rear factory hole with the factory bolt (closest to the outside of the car) then move to the rear inside and continue in a counter-clockwise pattern. Continue to slightly tighten all of the factory bolts into the factory hole locations.



### STEP 7

(View of the front of the seat)

Line up the factory seat to the new hole locations (4" back from the factory holes). Tighten the two front seat "feet" into the new ExtendMySeat hole locations using the ExtendMySeat bolts.



### STEP 8

(View from backseat) Use one of the black bolts.



### STEP 8 cont.

(View from backseat) Use the one hex nut to secure the inner rear location.

Slide the seat all the way forward and go the backseat of the car to secure the last two remaining ExtendMySeat bolts into the two ExtendMySeat holes.



### STEP 9

Complete the installation by securing the eight bolts (four factory and four ExtendMySeat). Check to make sure all eight bolts are now tight and secure.

### STEP 10

Re-install two rear factory plastic guards

### STEP 11

Test seat by sliding it back and forth. You are complete.

### MORE INFORMATION

To view a video  
on installation, please visit  
[extendmyseat.com](http://extendmyseat.com/install-guides/)  
/install-guides/

**EXTENDMYSEAT.COM**  
3186-H Airway Avenue  
Costa Mesa, California 92626