

Thank You

Thank you for ordering brackets from ExtendMySeat, the automotive solution for more leg-room, more comfort and better driving.

Inventory in Box:

- 3 ExtendMySeat brackets
- 4 3/8 black bolts

Optional - small flat metal piece for passenger installation with JBL sound package.

What you will need for assembly:

- 1 Socket wrench
- 1 Metric 14 socket

STEP 1

Remove the ExtendMySeat brackets from the package and locate the four black bolts provided.

STEP 2





STEP 2 cont.

Use a socket wrench to remove the two factory bolts in the front seat then slide your seat forward.

STEP 3

Move to the backseat and remove the two plastic guards then locate and remove the two rear factory bolts.

STEP 4



*This demo vehicle has the navigation package. You may or may not have a box under your seat.

Move your seat all the way back to lift the front of your seat up so you can slide the ExtendMySeat brackets under the seat.

STEP 5

Lay down the ExtendMySeat brackets like the image below for the driver's side installation (passenger side layout is flipped so the one long bracket is installed towards the outside of the car).

STEP 6

Inside of Vehicle

Rear of Vehicle

See step 6B

Start by slightly tightening the rear factory hole with the factory bolt (closest to the outside of the car) then slightly tighten the two front factory locations using the factory bolts. You may or may not have a small electrical box under your seat, depending on your model. If you have an electrical box under your seat, please follow Step 6B.

STEP 6B



STEP 6B cont.

We have a video online explaining this step. Please visit our YouTube channel for the ExtendMvSeat navigation video.

- 1 Remove the black cover.
- 2 Unscrew both of the two (BIG) bolts securing the electrical box bracket to the floor.
- 3 Move the electrical box (including bracket) over one bolt to the left and secure to the floor with just the one bolt. The main part of the electrical box bracket will not be bolted. This will leave only one big bolt to secure the electrical box (more than enough support to secure the electrical box).
- 4 Install the ExtendMySeat front B bracket (smaller non 90 degree angled bracket).

STEP 7



Go to the front seat and align the seat with the new ExtendMySeat hole locations. Slightly tighten the two front seat "feet" into the new ExtendMySeat hole locations using the ExtendMySeat bolts.

STEP 8



Slide the seat all the way forward and go to the backseat to secure the remaining two factory "feet" with the factory bolts.

STEP 9

Lexus CT 200 H (2011 to present) Extender Guide

Toyota Prius GEN 3 (2010-2013) Driver & Passenger Side,

Complete the installation by securing all eight bolts (four factory and four ExtendMySeat). Check to make sure all eight bolts are tight and secure.

STEP 10

Re-install two factory plastic guards.

STEP 11

Test seat by sliding it back and forth. You are complete.

MORE INFORMATION

To view a video on installation, please visit extendmyseat.com/ install-guides/

If you are installing the passenger side, repeat the above steps on the passenger side.

EXTENDMYSEAT.COM 3186-H Airway Avenue Costa Mesa, California 92626