INSTALLATION GUIDE Highlander (2009-2012)



Toyota Highlander Extender Guide Installation Guide: Thank you for purchasing ExtendMySeat (EMS) brackets. Please follow the directions carefully and within 30 minutes you will be loving your new seats.

Inventory in Box:

- 3 ExtendMySeat brackets
- 4 Black 3/8 stainless bolts

What you will need for assembly:

1- Socket wrench

1- Metric 14mm socket (Prius uses metric however a 9/16 works)

<u>Step 1-</u> Remove the Black ExtendMySeat brackets from the packaging and locate the clear bolt baggie.

<u>Step 2-</u> Go to your vehicle with a socket wrench and a metric 14 socket, eye protection and your keys. Remember to turn off your cabin lights.

<u>Step 3-</u> Locate the 4 factory bolts that hold your seat to the vehicle. Take your socket wrench and loosen the 4 factory bolts. (2 in the front and 2 behind your seat, go to rear seat to locate) Remove the 2 plastic guards to locate the 2 rear factory bolts (it helps to remove by pulling clockwise). Remove the 4 factory bolts and set them aside



<u>Step 7-</u> Start with the front 2 brackets. Grab the 2 "shorter" ExtendMySeat brackets.

<u>Step 8-</u> Move your seat all the way back. Now lift the front of your seat up so you can slide the brackets under the front of the OEM seat.



Lay down the 2 black brackets inside your vehicle and line up the 2 OEM hole locations. The bracket bends will face inward.

Start with the front 2 holes. Finger tighten the 2 factory bolts into the 2 front EMS bracket holes.



Grab the larger 1 piece bracket. Lay it down in the rear area. Now line up the 2 rear OEM holes and finger tighten the 2 remaining factory bolts.



<u>Step 9-</u> In the front area; lay your factory seat on top of the EMS brackets and line up seat front holes with EMS front holes. Finger tighten front 2 feet with provided black EMS bolts.

<u>Step 10-Press seat lever and slide seat to</u> the most up front position. Go to back seat and screw down the remaining 2 factory feet with the stainless EMS bolts.

<u>Step 11-</u> Make sure all 8 bolts are tight.

<u>Step 12-</u> Test the seat by sliding the seat back and forth.

Step 13- Enjoy!